ADMIN: Phone: (07) 3895 9800 Fax: (07) 3895 9801 SALES: Phone: (07) 3985 9890 Fax: (07) 3895 9891

## **Certificate Of Analysis**

Certificate Number: 0127-23 Issue Number: 1 Issue Date: 17/05/2023 11:04:43 AM

Test Certificate for: Flyash Blend 25

Sample Produced at:

Sample Tested at: Sunstate Cement Ltd., Port of Brisbane, Australia Sample Identification: Spot Despatch Sample F6P-001671 dated 10/04/2023 Sunstate Cement Ltd., Port of Brisbane, Australia

SPECIFIC PROPERTY	TEST METHOD	AS3972 REQUIREMENTS		RESULT
Compressive strength	AS2350.11, AS2350.12			
3 Day				<b>25.4</b> MPa
7 Day		Minimum	35 MPa	<b>37.4</b> MPa
28 Day		Minimum	45 Mpa	<b>54.2</b> MPa
Setting Time	AS2350.4			
Inital		Minimum	45 mins	<b>105</b> mins
Final		Maximum	360 mins	<b>195</b> mins
Soundness	AS2350.5	Maximum	5 mm	2 mm
Sulphuric anhydride (SO₃)	In House	Maximum	3.5 %	2.2 %
Chloride	AS3583.13	Maximum	0.1 %	0.004 %
REPORTABLE PROPERTY	TEST METHOD			RESULT
Loss on ignition	AS2350.2			2.2 %
Fineness	AS2350.8			<b>445</b> m²/kg
OTHER PROPERTIES	TEST METHOD			RESULT
Normal Consistency	AS2350.3	,		30.1 %

## **Sampling Procedure:**

Samples were prepared in accordance with AS2350.1

- 1 These results only relate to the specimens identified on this
- 2 The sample as tested conforms to the requirements of AS3972 as Type GB cement
- 3 The blended cement is produced with as nominal 25% fly ash content



NATA accredited Laboratory Number: 2191

Accredited for compliance with ISO/IEC 17025 Testing



**Approved Signature** 17/05/2023