ADMIN: Phone: (07) 3895 9800 Fax: (07) 3895 9801 SALES: Phone: (07) 3985 9890 Fax: (07) 3895 9891

Certificate Of Analysis

Certificate Number: **0025-24** Issue Number: **1** Issue Date: **9/04/2024 9:39:29 AM**

Test Certificate for: **GP Cement**

Sample Tested at: Sunstate Cement Ltd., Port of Brisbane, Australia
Sample Identification: Spot Despatch Sample A6P-003202 dated 15/01/2024

Sample Produced at: Sunstate Cement Ltd., Port of Brisbane, Australia

SDECIFIC DRODERTY	TEST METHOD AS3972 REQUIREMENTS RESULT			
SPECIFIC PROPERTY		AS3972 REQUIREMENTS		RESULT
Compressive strength	AS2350.11, AS2350.12			
3 Day				31.7 MPa
7 Day		Minimum	35 MPa	43.7 MPa
28 Day		Minimum	45 Mpa	61.1 MPa
Setting Time	AS2350.4			
Inital		Minimum	45 mins	105 mins
Final		Maximum	360 mins	150 mins
Soundness	AS2350.5	Maximum	5 mm	2 mm
Sulphuric anhydride (SO₃)	In House	Maximum	3.5 %	2.8 %
Chloride	AS3583.13	Maximum	0.1 %	0.020 %
REPORTABLE PROPERTY	TEST METHOD			RESULT
Loss on ignition	AS2350.2			3.9 %
Fineness	AS2350.8			370 m ² /kg
Total Alkali	AS2350.2			0.5 %
OTHER PROPERTIES	TEST METHOD			RESULT
Normal Consistency	AS2350.3			28.3 %

Sampling Procedure:

Samples were prepared in accordance with AS2350.1

Remarks:

- 1 These results only relate to the specimens identified on this report
- 2 Total Alkali determined at Australian Laboratory Services by ICP-AES using ME-ICP 91, Corporate Accreditation No. 825, Corporate Site No. 818



NATA accredited Laboratory Number: 2191

Accredited for compliance with ISO/IEC 17025 Testing

