

Certificate Of Analysis

Certificate Number:0089-24Issue Number:2Issue Date:9/04/2024 9:24:33 AMTest Certificate for:Slag Blend 60Sample Tested at:Sunstate Cement Ltd., Port of Brisbane, AustraliaSample Identification:Spot Despatch Sample H6P-000802 dated 27/02/2024Sample Produced at:Sunstate Cement Ltd., Port of Brisbane, Australia

SPECIFIC PROPERTY	TEST METHOD	AS3972 REQUIREMENTS		RESULT
Compressive strength	AS2350.11, AS2350.12			
3 Day				16.9 MPa
7 Day		Minimum	20 MPa	29.3 MPa
28 Day		Minimum	35 Mpa	50.9 MPa
Setting Time	AS2350.4			
Inital		Minimum	45 mins	135 mins
Final		Maximum	600 mins	225 mins
Soundness	AS2350.5	Maximum	5 mm	2 mm
Sulphuric anhydride (SO₃)	In House	Maximum	3.5 %	2.7 %
Chloride	AS3583.13	Maximum	0.1 %	0.009 %
REPORTABLE PROPERTY	TEST METHOD			RESULT
Loss on ignition	AS2350.2			0.8 %
Fineness	AS2350.8			475 m²/kg
OTHER PROPERTIES	TEST METHOD			RESULT
Normal Consistency	AS2350.3			33.3 %

Sampling Procedure:

Samples were prepared in accordance with AS2350.1

Remarks:

1 These results only relate to the specimens identified on this report



NATA accredited Laboratory Number: 2191

Accredited for compliance with ISO/IEC 17025 Testing

George Santagiuliana Approved Signature 09/04/2024