ADMIN: Phone: (07) 3895 9800 Fax: (07) 3895 9801 SALES: Phone: (07) 3985 9890 Fax: (07) 3895 9891

Certificate Of Analysis

Certificate Number: **0458-20** Issue Number: **1** Issue Date: **10/09/2020 9:27:06 AM**

Test Certificate for: Flyash Blend 25

Sample Produced at:

Sample Tested at: Sunstate Cement Ltd., Port of Brisbane, Australia
Sample Identification: Spot Despatch Sample F6P-001378 dated 18/05/2020

Sunstate Cement Ltd., Port of Brisbane, Australia

SPECIFIC PROPERTY	TEST METHOD AS2350.11, AS2350.12	AS3972 REQUIREMENTS		RESULT
Compressive strength				
3 Day				26.6 MPa
7 Day		Minimum	35 MPa	39 MPa
28 Day		Minimum	45 Mpa	54.6 MPa
Setting Time	AS2350.4			
Inital		Minimum	45 mins	105 mins
Final		Maximum	360 mins	195 mins
Soundness	AS2350.5	Maximum	5 mm	1 mm
Sulphuric anhydride (SO₃)	In House	Maximum	3.5 %	1.9 %
Chloride	AS3583.13	Maximum	0.1 %	0.003 %
REPORTABLE PROPERTY	TEST METHOD			RESULT
Loss on ignition	AS2350.2			1.9 %
Fineness	AS2350.8			435 m²/kg
OTHER PROPERTIES	TEST METHOD			RESULT
Normal Consistency	AS2350.3			30.8 %

Sampling Procedure:

Samples were prepared in accordance with AS2350.1

Remarks:

- 1 These results only relate to the specimens identified on this report
- 2 The sample as tested conforms to the requirements of AS3972 as Type GB cement
- 3 The blended cement is produced with as nominal 25% fly ash content



NATA accredited Laboratory Number: 2191

Accredited for compliance with ISO/IEC 17025 Testing

George Santagiuliana Approved Signature

10/09/2020